



TECHNICA
DEL ARTE

Luci URI reference

luci: <host> [: <port>] [? <query>]

Example

luci:echo.lucilive.com:5042?Name=clicktoecho

Define extra parameters

luci:echo.lucilive.com:5042?Name=clicktoecho&par1=value1&par2=value2 etc...

Parameters reference

All Case-dependent !!

| | |
|----------------|---|
| Name | Display name, default=host:port |
| Channels | 1 (default) , 2 |
| Samplerate | 44100 , 48000 (default) |
| Bitdepth | 16 (default) , 24 |
| Protocol | 32 (RTP)(default) , 34(N/ACIP) |
| Codec | 0(MP2) , 3 (AAC-HE)(default) , 4(AAC-HEV2) , 9(G722) , 10(L16) |
| Bitrate | a number like 24000 , 32000 , 48000 etc, default= 32000 |
| Jitterbuffer | a number in ms, default= 100 |
| Jitterbuffer3G | a number in ms, default= 200 |

Example

luci:echo.lucilive.com:5042?Name=clicktoecho&Protocol=32&Codec=0&Bitrate=80000&Jitterbuffer=50

You can use Escape sequences also. So, in order to define spaces you use escape sequence %20 , the same as webpage URL's:

luci:echo.lucilive.com:5042?Name=Echo%20Server%20Via%20Web

Will create a station called "Echo Server Via Web"